# **Installation Instructions**

安裝說明書

前可調李仔串 #8783


## Application 適用車型

Lexus IS '05-13 Lexus GS '05-12

# Components 內含配件

① Stabilizer end link 李仔串

2PCS



#### Caution 注意事項

- •Installation is recommended to be performed by licensed mechanics with necessary tools to ensure proper installation and safety, or damage to the product or vehicle may occur.
- •Note the routing and position of wires and cables before installation. Please refer to factory manual.
- •Tighten bolts and nuts frimly using handtools, or with specified torque if mentioned.
- 安裝需由合格的專業技師及工具執行以確保安裝正確及安全 否則可能對產品或車輛造成傷害。
- 安裝前請記下線路安裝路徑及位置,或請參考原廠手冊。
- 請使用手動工具確實鎖緊螺帽及螺絲,或依照說明中標註的扭力上鎖。

## Instructions 安裝說明

- 1. Remove the factory front stabilizer links from the lower control arms and stabilizer bar on both sides. (See figure 1) 將左右兩側原廠的前李仔串由前下控制臂以及防傾桿卸下。 (請參考圖表一)
- 2. Loosen the nuts on ①Stabilizer end links to adjust the length and angle , then install the links to the vehicle using the removed nuts. Please install the ends with longer studs to the lower control arms and the shorter to the stabilizer bar. (See figure 2)

鬆開 ①李仔串 螺帽後調整桿身長度及角度,並將李仔串使用已拆下的螺帽 裝上車輛,請注意將螺柱較長的一端安裝於下控制臂,較短的一端則安裝於 防傾桿桿身。(請參考圖表二)

Illstration of installed state 完成示意圖

Note 提示 -

The stabilizer end link is designed for lowered vehicles to correct the position of the stabilizer bar. With adjustable function it provides slight adjustment range to accomodate unequal ride height between the sides.

此李仔串適用於降低車高的車輛,桿身的長度可依照車輛左右邊的高 低落差細微調整。

